

**GlasSeal (NI) Ltd.**

80 Belfast Road, Ballynahinch, Co.Down, Northern Ireland, United Kingdom. BT24 8EB

01/07/2013

EN 1279-5

Insulating glass units intended to be used in buildings and construction works

6.4mm Laminated/12mm Argon 90% Low-E/6.4mm Laminated [24.8mm]
GS-DGU 331-AR12LE-331*Characteristics:***For uses relating to safety in case of fire**

Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD

For uses as anti-bullet or anti-explosion glazing

Bullet resistance	NPD
Explosion resistance	NPD

For uses liable to present "safety-in-use" risks and subject to such regulations

Burglar resistance	NPD / NPD
Pendulum body impact resistance	2(B)2 / 2(B)2
Resistance against sudden temperature changes and temperature differentials	40K / 40K
Wind, snow, permanent and imposed load resistance (mm)	6.4/12/6.4

For uses relating to noise reduction

Direct airborne sound insulation (dB)	NPD
---------------------------------------	-----

For uses relating to energy consumption

Emissivity ϵ_d	NPD
U value (W/m^2K)	1.3
Light transmittance τ_L	NPD
Light reflection ρ_L	NPD
Solar energy transmission τ_E	NPD
Solar energy reflection ρ_L	NPD
Solar factor g	NPD

Dangerous Substances:

Dangerous substances	No
----------------------	----

NPD : No Performance Declared